

View Online at <https://aerobasegroup.com/nsn/5930-00-828-0605>

Inside Diameter:

0.250 inches single connection

Overall Length:

4.375 inches

Overall Height:

7.500 inches

Overall Width:

2.875 inches

Body Height:

5.500 inches

Longest Horizontal Distance Between Mounting Centers:

2.500 inches

Longest Vertical Distance Between Mounting Centers:

3.500 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 35.0 degrees fahrenheit and 95.0 degrees fahrenheit

Mounting Method:

Threaded hole and base

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

40000.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.5 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+100.00/+12000.00 actuation point pounds per square inch gage and +100.00/+12000.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0