

View Online at <https://aerobasegroup.com/nsn/5930-00-828-2296>

Thread Class:

2b all threaded hole

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

4.750 inches

Overall Height:

4.125 inches

Overall Width:

2.250 inches

Longest Horizontal Distance Between Mounting Centers:

3.500 inches

Longest Vertical Distance Between Mounting Centers:

2.562 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and threaded hole

Thready Qty Per Inch (tpi):

20 all threaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+50.00/+65.00 actuation point pounds per square inch and +50.00/+65.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

15.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0