NSN 5930-00-828-6728

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-828-6728

Body Style:					
Hole mounted					
Center To Center Distance Between Mounting Facilities Parallel To Length:					
0.520 inches					
Body Length:					
1.250 inches					
Body Width:					
0.500 inches					
Body Height:					
0.500 inches					
Case Material:					
Metal					
Unthreaded Mounting Hole Diameter:					
0.101 inches					
Center To Center Distance Between Mounting Facilities Parallel To Height:					
0.312 inches					
Actuator Length:					
0.855 inches					
Actuator Style:					
Roller arm					
Actuator Free Position Height:					
0.746 inches					
Actuator Roller Diameter:					
0.375 inches					
Actuator Roller Width:					
0.187 inches					
Maximum Voltage Rating In Volts:					
250.0 ac and 250.0 dc					
End Application:					
Truck lift fork					
Inclosure Type:					
Fully enclosed					
Nonpile-up Contact Arrangement:					
1 pole, double throw, double break/double make, one position momentary single switch unit					
Switch Release Force:					
2.0 ounces					
Switch Actuating Force:					
3.5 ounces					
Actuator Movement:					
Between 0.093 pretravel inches and 0.062 overtravel inches and 0.046 differential inches					
Contact Load Current Rating At Maximum Rated Voltage:					

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

NSN 5930-00-828-6728

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity	Terminal	Type	And	Quantity
----------------------------	----------	------	-----	----------

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0