

View Online at <https://aerobasegroup.com/nsn/5930-00-829-3238>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

7.500 inches

Overall Height:

9.390 inches

Unthreaded Mounting Hole Diameter:

0.518 inches single mounting facility and 0.525 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

5.625 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.625 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section front

Throw Quantity:

4 single section rear

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Metallic inclosure

Contact Voltage Rating In Volts:

450.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Contact Switching Action:

Breaks before makes single section rear

Contact Load Current Rating:

200.0 amperes resistive load ac at sea level and 200.0 amperes inductive load ac at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0