

View Online at <https://aerobasegroup.com/nsn/5930-00-829-3238>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

7.500 inches

**Overall Height:**

9.390 inches

**Unthreaded Mounting Hole Diameter:**

0.518 inches single mounting facility and 0.525 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

5.625 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.625 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section front

**Throw Quantity:**

4 single section rear

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Metallic inclosure

**Contact Voltage Rating In Volts:**

450.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Contact Switching Action:**

Breaks before makes single section rear

**Contact Load Current Rating:**

200.0 amperes resistive load ac at sea level and 200.0 amperes inductive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Test Data Document:**

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A052b0