

View Online at <https://aerobasegroup.com/nsn/5930-00-829-3748>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Submersible

**Overall Length:**

1.281 inches

**Overall Height:**

2.179 inches

**Overall Width:**

0.719 inches

**Bushing Length:**

Between 0.450 inches and 0.490 inches

**Body Length:**

1.281 inches

**Body Width:**

0.719 inches

**Body Height:**

0.719 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.235 inches and 0.245 inches

**Actuator Height:**

Between 0.660 inches and 0.720 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

220.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.500 amperes inductive dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac

**Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0