NSN 5930-00-829-8771

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-829-8771

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.652 inches

Body Length:

0.781 inches

Body Width:

0.562 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.500 inches

Actuator Style:

Leaf

Actuator Width:

0.156 inches

Actuator Free Position Height:

0.562 inches

Actuator Adapter Style:

Nonadjustable arm

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.094 pretravel inches and 0.031 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac

NSN 5930-00-829-8771

Sensitive Switch - Page 2 of 2



Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0