NSN 5930-00-829-8771

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-829-8771

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.652 inches
Body Length:
0.781 inches
Body Width:
0.562 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.500 inches
Actuator Style:
Leaf
Actuator Width:
0.156 inches
Actuator Free Position Height:
0.562 inches
Actuator Adapter Style:
Nonadjustable arm
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
10.0 ounces
Actuator Movement:
Between 0.094 pretravel inches and 0.031 overtravel inches and 0.015 differential inches
Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac

NSN 5930-00-829-8771 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0