

View Online at <https://aerobasegroup.com/nsn/5930-00-831-2787>

Thread Class:

2b 1st mounting facility

Thread Length:

0.500 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

14.030 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

Shaft Length:

2.530 inches single actuator

Individual Section Quantity:

25

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

G

Longest Horizontal Distance Between Mounting Centers:

2.300 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.300 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded stud 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

56 2nd mounting facility

Thread Size:

0.190 inches 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks, breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Precious Material And Location:

Rotor and stator contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc 2nd mounting facility

Specification Data:

81349-mil-s-21604/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0