

View Online at <https://aerobasegroup.com/nsn/5930-00-831-5229>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

3.125 inches

**Overall Height:**

1.500 inches

**Overall Width:**

1.937 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

2.250 inches single actuator

**Nonturn Device Radius:**

0.437 inches at 9: 00 o'clock

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

71590

**Knob Manufacturer Part Number:**

P-120

**Nonturn Device Type:**

Tab at 9: 00 o'clock

**Operating Temperature Range:**

-65.0/+175.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 single section front

**Throw Quantity:**

6 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Actuator knob

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

24.0 highest dc voltage rating at sea level

**Rotor Through Connection Quantity:**

2 single section

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

5.5 amperes resistive load highest dc voltage rating at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0