## NSN 5930-00-831-5231

Rotary Switch - Page 1 of 2

**Thread Class:** 

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-831-5231

Thread Length: 0.375 inches single mounting facility **Overall Length:** 3.125 inches **Overall Height:** 1.500 inches **Overall Width:** 1.312 inches **Nonturn Device Radius:** 0.437 inches at 9: 00 o'clock **Individual Section Quantity: Knob Manufacturer Code:** 71590 **Knob Manufacturer Part Number:** P-120 **Nonturn Device Type:** Tab at 9: 00 o'clock **Operating Tempurature Range:** -65.0/+175.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section front **Throw Quantity:** 12 single section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 

Rotor Through Connection Quantity:
1 single section

**Switch Actuator Indexing Position Quantity:** 

6.0 lowest dc voltage rating at sea level

12 single actuator

**Terminal Type:** 

Tab, solder lug

## NSN 5930-00-831-5231

Rotary Switch - Page 2 of 2



Contact Switching Action:
---------------------------

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Contact Load Current Rating:** 

5.5 amperes resistive load highest dc voltage rating at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0