NSN 5930-00-831-6437

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-831-6437

| Body Style: | | |
|--|--|--|
| Bushing mount | | |
| Overall Length: | | |
| 0.719 inches | | |
| Overall Height: | | |
| 2.234 inches | | |
| Overall Width: | | |
| 0.844 inches | | |
| Bushing Length: | | |
| 0.469 inches | | |
| Body Length: | | |
| 0.844 inches | | |
| Body Width: | | |
| 0.844 inches | | |
| Body Height: | | |
| 1.078 inches | | |
| Actuator Style: | | |
| Round | | |
| Actuator Diameter: | | |
| 0.240 inches | | |
| Actuator Height: | | |
| 0.687 inches | | |
| Actuator Position-action Relationship: | | |
| Up position momentary and down position momentary and center position maintained | | |
| Actuator Position-locking Relationship: | | |
| Center position locked in | | |
| Maximum Voltage Rating In Volts: | | |
| 115.0 ac and 28.0 dc | | |
| Inclosure Type: | | |
| Uninclosed | | |
| Mounting Method: | | |
| Threaded bushing | | |
| Thready Qty Per Inch (tpi): | | |
| 32 | | |
| Thread Size: | | |
| 0.469 inches | | |
| Nonpile-up Contact Arrangement: | | |
| 2 pole, double throw, both positions maintained single switch unit | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | |
| 3.000 amperes resistive dc and 5.000 amperes resistive ac | | |

Uns

Thread Series Designator:

NSN 5930-00-831-6437 Toggle Switch - Page 2 of 2



| Terminal ' | Type And | Quantity: |
|--------------|------------|------------|
| ı errillinar | I VDE AIIU | Qualitity. |

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0