

View Online at <https://aerobasegroup.com/nsn/5930-00-832-5174>

Thread Class:

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

2.151 inches

First Flat Length:

0.400 inches single actuator and 0.447 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.247 inches single actuator

Shaft Length:

0.531 inches single actuator

Overall Diameter:

1.950 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

7 each section front

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Detent Rotational Torque Range:

+3.000/+6.000 inch-pounds single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level and 2.0 amperes lamp load dc at sea level

Precious Material And Location:

Terminal surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0