

View Online at <https://aerobasegroup.com/nsn/5930-00-832-8361>

Hazardous Locations/environmental Protection:

Vibration resistant and dustproof

Overall Height:

0.750 inches

Overall Width:

0.625 inches

Body Length:

1.219 inches

Unthreaded Mounting Hole Diameter:

0.122 inches

Longest Horizontal Distance Between Mounting Centers:

0.344 inches

Longest Vertical Distance Between Mounting Centers:

0.938 inches

Operating Temperature Rating:

125.0 degrees celsius and -65.0 degrees celsius

Mounting Method:

Unthreaded hole

Features Provided:

Automatic reset

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

4.00 actuation point gram and 0.50 deactuation point gram

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0