

View Online at <https://aerobasegroup.com/nsn/5930-00-832-8361>

**Hazardous Locations/environmental Protection:**

Vibration resistant and dustproof

**Overall Height:**

0.750 inches

**Overall Width:**

0.625 inches

**Body Length:**

1.219 inches

**Unthreaded Mounting Hole Diameter:**

0.122 inches

**Longest Horizontal Distance Between Mounting Centers:**

0.344 inches

**Longest Vertical Distance Between Mounting Centers:**

0.938 inches

**Operating Temperature Rating:**

125.0 degrees celsius and -65.0 degrees celsius

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Automatic reset

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

4.00 actuation point gram and 0.50 deactuation point gram

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0