

View Online at <https://aerobasegroup.com/nsn/5930-00-833-3156>

Body Style:

Hole mounted

Overall Length:

Between 0.771 inches and 0.791 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.373 inches and 0.377 inches

Overall Height:

Between 0.492 inches and 0.542 inches

Overall Width:

Between 0.240 inches and 0.260 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.346 inches and 0.366 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Height:

Between 0.0230 inches and 0.033 inches

Actuator Free Position Height:

Between 0.315 inches and 0.345 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

3.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0