

View Online at <https://aerobasegroup.com/nsn/5930-00-834-4809>

**Overall Length:**

Between 1.230 inches and 1.270 inches

**Overall Height:**

0.440 inches

**Overall Width:**

Between 0.380 inches and 0.420 inches

**Body Length:**

Between 0.760 inches and 0.800 inches

**Body Width:**

Between 0.380 inches and 0.420 inches

**Body Height:**

Between 0.230 inches and 0.270 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 0.990 inches and 1.010 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.5 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

-20.00/+275.00 actuation point degrees fahrenheit

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Style Designator:**

Rectangular w/bracket

**Test Data Document:**

89661-788c284 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0