NSN 5930-00-835-9945

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-835-9945

Body Style:

Hole mounted

Overall Length:

1.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.297 inches

Overall Width:

0.688 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Body Height:

0.953 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.093 inches

Actuator Free Position Height:

0.625 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

24.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes motor dc and 10.000 amperes resistive ac and 10.000

amperes inductive ac and $5.000 \ \mbox{amperes}$ motor ac

Terminal Type And Quantity:

3 screw

NSN 5930-00-835-9945

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

