

View Online at <https://aerobasegroup.com/nsn/5930-00-836-3334>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.520 inches

Bushing Length:

0.500 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Body Height:

0.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.312 inches

Actuator Style:

Round

Actuator Diameter:

0.278 inches

Actuator Height:

0.328 inches

Actuator Free Position Height:

1.220 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

0.500 inches

Maximum Voltage Rating In Volts:

250.0 ac and 125.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action single switch unit

Switch Release Force:

48.0 ounces

Switch Actuating Force:

16.0 ounces

Actuator Movement:

0.050 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 10.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0