## NSN 5930-00-836-6564

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-836-6564

Hole mounted  Case Material: Metal  Actuator Style: Round  Actuator Diameter: 0.328 inches  Actuator Free Position Height: 1.719 inches  Housing Width: 1.000 inches  Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches  Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches  Maximum Voltage Rating In Volts: 480.0 ac and 250.0 dc Inclosure Type: Fully enclosed  Mounting Method: Unthreaded hole  Thready Qty Per Inch (tpi): 32  Thread Size: 0.138 inches  Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: 31.0 ounces  Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 6 screw  Shelf Life: N/a  Unit Of Measure:	Body Style:
Metal Actuator Style: Round Actuator Diameter: 0.328 inches Actuator Free Position Height: 1.719 inches Housing Width: 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches Maximum Voltage Rating In Volts: 480.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Hole mounted
Actuator Style: Round Actuator Diameter: 0.328 inches Actuator Free Position Height: 1.719 inches Housing Width: 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches Maximum Voltage Rating In Volts: 480.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Thready Oty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Case Material:
Round Actuator Diameter: 0.328 inches Actuator Free Position Height: 1.719 inches Housing Width: 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches Maximum Voltage Rating In Volts: 480.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Metal
Actuator Diameter: 0.328 inches Actuator Free Position Height: 1.719 inches Housing Width: 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches Maximum Voltage Rating In Volts: 480.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Thready Oty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Actuator Style:
0.328 inches Actuator Free Position Height: 1.719 inches Housing Width: 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches Maximum Voltage Rating In Volts: 480.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Thready Oty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Round
Actuator Free Position Height:  1.719 inches  Housing Width:  1.000 inches  Center To Center Distance Between Housing Mounting Facilities Parallel To Length:  1.000 inches  Maximum Voltage Rating In Volts:  480.0 ac and 250.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Unthreaded hole  Thready Qty Per Inch (tpi):  32  Thread Size:  0.138 inches  Nonpile-up Contact Arrangement:  2 pole, double throw, one position momentary single switch unit  Switch Release Force:  4.0 ounces  Switch Actuating Force:  31.0 ounces  Actuator Movement:  Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator:  Unc  Terminal Type And Quantity: 6 screw  Shelf Life:  N/a	Actuator Diameter:
1.719 inches Housing Width: 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches Maximum Voltage Rating In Volts: 480.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	0.328 inches
Housing Width:  1.000 inches  Center To Center Distance Between Housing Mounting Facilities Parallel To Length:  1.000 inches  Maximum Voltage Rating In Volts:  480.0 ac and 250.0 dc Inclosure Type:  Fully enclosed  Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi):  32  Thread Size: 0.138 inches  Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: 31.0 ounces  Actuator Movement:  Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 6 screw  Shelf Life: N/a	Actuator Free Position Height:
1.000 inches  Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches  Maximum Voltage Rating In Volts: 480.0 ac and 250.0 dc Inclosure Type: Fully enclosed  Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	1.719 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:  1.000 inches  Maximum Voltage Rating In Volts:  480.0 ac and 250.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Unthreaded hole  Thready Qty Per Inch (tpi): 32  Thread Size: 0.138 inches  Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: 31.0 ounces  Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 6 screw  Shelf Life: N/a	Housing Width:
1.000 inches  Maximum Voltage Rating In Volts:  480.0 ac and 250.0 dc  Inclosure Type:  Fully enclosed  Mounting Method: Unthreaded hole  Thready Qty Per Inch (tpi):  32  Thread Size: 0.138 inches  Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: 31.0 ounces  Actuator Movement:  Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 6 screw  Shelf Life: N/a	1.000 inches
Maximum Voltage Rating In Volts:  480.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
480.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	1.000 inches
Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Maximum Voltage Rating In Volts:
Fully enclosed  Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	480.0 ac and 250.0 dc
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Inclosure Type:
Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Fully enclosed
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Mounting Method:
Thread Size: 0.138 inches  Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: 31.0 ounces  Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 6 screw  Shelf Life: N/a	Unthreaded hole
Thread Size:  0.138 inches  Nonpile-up Contact Arrangement:  2 pole, double throw, one position momentary single switch unit  Switch Release Force:  4.0 ounces  Switch Actuating Force:  31.0 ounces  Actuator Movement:  Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator:  Unc  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a	Thready Qty Per Inch (tpi):
Nonpile-up Contact Arrangement:  2 pole, double throw, one position momentary single switch unit  Switch Release Force:  4.0 ounces  Switch Actuating Force:  31.0 ounces  Actuator Movement:  Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator:  Unc  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a	32
Nonpile-up Contact Arrangement:  2 pole, double throw, one position momentary single switch unit  Switch Release Force:  4.0 ounces  Switch Actuating Force:  31.0 ounces  Actuator Movement:  Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator:  Unc  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a	Thread Size:
2 pole, double throw, one position momentary single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: 31.0 ounces  Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 6 screw  Shelf Life: N/a	0.138 inches
Switch Release Force:  4.0 ounces  Switch Actuating Force:  31.0 ounces  Actuator Movement:  Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator:  Unc  Terminal Type And Quantity:  6 screw  Shelf Life:  N/a	Nonpile-up Contact Arrangement:
Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	2 pole, double throw, one position momentary single switch unit
Switch Actuating Force: 31.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 125.000 milliamperes resistive dc and 15.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Switch Release Force:
31.0 ounces  Actuator Movement:  Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator:  Unc  Terminal Type And Quantity: 6 screw  Shelf Life:  N/a	4.0 ounces
Actuator Movement:  Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator:  Unc  Terminal Type And Quantity: 6 screw  Shelf Life:  N/a	Switch Actuating Force:
Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator:  Unc  Terminal Type And Quantity: 6 screw  Shelf Life:  N/a	31.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:  125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator:  Unc  Terminal Type And Quantity: 6 screw  Shelf Life:  N/a	Actuator Movement:
125.000 milliamperes resistive dc and 15.000 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 6 screw  Shelf Life: N/a	Between 0.078 pretravel inches and 0.219 overtravel inches and 0.003 differential inches
Thread Series Designator: Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	Contact Load Current Rating At Maximum Rated Voltage:
Unc Terminal Type And Quantity: 6 screw Shelf Life: N/a	125.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity: 6 screw Shelf Life: N/a	Thread Series Designator:
6 screw  Shelf Life: N/a	Unc
Shelf Life: N/a	Terminal Type And Quantity:
N/a	6 screw
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

--

## NSN 5930-00-836-6564

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0