# NSN 5930-00-836-6734

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-836-6734

### **Thread Class:**

2a single mounting facility

#### Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

1.594 inches

#### **Overall Height:**

1.156 inches

#### **Overall Width:**

1.125 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.375 inches single actuator

#### Individual Section Quantity:

1

# Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 single section rear

#### Throw Quantity:

2 single section front

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Makes before breaks single section front

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# **Contact Load Current Rating:**

0.5 amperes resistive load dc at sea level

# NSN 5930-00-836-6734

Rotary Switch - Page 2 of 2



**Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Square wafer, panel mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0