

View Online at <https://aerobasegroup.com/nsn/5930-00-837-2395>

**Thread Class:**

3b single pressure connection

**Thread Length:**

0.375 inches all threaded hole

**Hazardous Locations/environmental Protection:**

Vibration resistant and dustproof

**Overall Length:**

2.562 inches

**Body Diameter:**

2.250 inches

**Body Length:**

1.781 inches

**Distance Between Mounting Facility Centers:**

1.875 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 70.0 degrees celsius

**Mounting Method:**

Bracket and threaded hole

**Features Provided:**

Electrical box connector

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

500.00 pounds per square inch

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Sensing Element Burst Pressure:**

750.00 pounds per square inch

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

0.5 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+0.30/+100.00 actuation point pounds per square inch and +0.30/+100.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

19.00 actuation point pounds per square inch gage and 3.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0