NSN 5930-00-837-3665

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-837-3665

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.998 inches and 1.002 inches
Bushing Length:
0.609 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
Between 0.800 inches and 0.840 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Roller plunger
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.188 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
13.0 ounces
Actuator Movement:
Between 0.015 pretravel inches and 0.141 overtravel inches and 0.002 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

NSN 5930-00-837-3665

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0