NSN 5930-00-837-6685

Rotary Switch - Page 1 of 2



930-00-837-6685

| View Online at https://aerobasegroup.com/nsn/5 |
|--|
| Thread Length: |
| 0.250 inches single mounting facility |
| First Flat Length: |
| 0.375 inches single actuator |
| Flat Height: |
| 0.219 inches single actuator |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 0.812 inches single actuator |
| Individual Section Quantity: |
| 2 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Throw Quantity: |
| 2 each section front |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Thread Size: |
| 0.375 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 15.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 8 single actuator |
| Shaft Type: |
| Round, flatted single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Breaks before makes each section front |
| Switch Actuator Positioning Increment: |
| 30.0 degrees single actuator |
| Contact Load Current Rating: |
| 2.0 amperes resistive load dc at sea level |
| Thread Series Designator: |
| Unef single mounting facility |
| Shelf Life: |
| N/a |

Unit Of Measure:

NSN 5930-00-837-6685

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0