

View Online at <https://aerobasegroup.com/nsn/5930-00-837-9079>

Body Style:

Hole mounted

Overall Length:

1.280 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.495 inches and 0.505 inches

Overall Height:

1.130 inches

Overall Width:

0.530 inches

Body Length:

1.280 inches

Body Width:

0.530 inches

Body Height:

0.910 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Actuator Style:

Round

Actuator Diameter:

0.290 inches

Actuator Height:

0.120 inches

Actuator Free Position Height:

0.505 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, both positions maintained single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

Between 23.0 ounces and 33.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.018 overtravel inches and 0.021 differential inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

8 tab, solder lug

Reference Number Differentiating Characteristics:

Fleet ballistic missile quality as identified by qualitycontrol no. Poso400702

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0