NSN 5930-00-837-9079

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-837-9079

Body Style:
Hole mounted
Overall Length:
1.280 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.495 inches and 0.505 inches
Overall Height:
1.130 inches
Overall Width:
0.530 inches
Body Length:
1.280 inches
Body Width:
0.530 inches
Body Height:
0.910 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.114 inches
Actuator Style:
Round
Actuator Diameter:
0.290 inches
Actuator Height:
0.120 inches
Actuator Free Position Height:
0.505 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, both positions maintained single switch unit
Switch Release Force:
3.0 ounces
Switch Actuating Force:
Between 23.0 ounces and 33.0 ounces
Actuator Movement:
Between 0.060 pretravel inches and 0.018 overtravel inches and 0.021 differential inches and 0.035 differential inches
Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

NSN 5930-00-837-9079

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
8 tab, solder lug
Reference Number Differentiating Characteristics:
Fleet ballistic missile quality as identified by qualitycontrol no. Poso400702
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0