## NSN 5930-00-839-5218

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-839-5218

Corrosion resistant
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.876 inches
Body Width:
0.346 inches
Body Height:
0.710 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.078 inches
Actuator Height:
0.050 inches
Actuator Free Position Height:
0.475 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
17.0 ounces
Actuator Movement:
Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Terminal Type And Quantity:
2 wire lead

## NSN 5930-00-839-5218

Sensitive Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0