

View Online at <https://aerobasegroup.com/nsn/5930-00-839-6675>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

0.986 inches

**Overall Width:**

0.952 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.125 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Operating Temperature Range:**

-8.0/+65.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, slotted single actuator

**Terminal Type:**

Tab, solder lug

**Detent Rotational Torque Range:**

+10.000/+20.000 inch-ounces single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Precious Material:**

Gold and silver

**Style Designator:**

Partial wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0