## NSN 5930-00-840-1986

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-840-1986

**Thread Class:** 

2a single mounting facility

Thread Length:

0.380 inches single mounting facility

**Overall Length:** 

1.660 inches

**Overall Height:** 

1.000 inches

**Overall Width:** 

0.938 inches

**Shaft Diameter:** 

0.219 inches single actuator

**Shaft Length:** 

0.430 inches single actuator

**Nonturn Device Radius:** 

0.380 inches at 10: 00 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Tab at 10: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

10 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Switch Actuator Positioning Increment:** 

36.0 degrees single actuator

**Contact Load Current Rating:** 

500.0 milliamperes resistive load ac at sea level

**Precious Material And Location:** 

Contact surfaces silver

**Precious Material:** 

Silver

## NSN 5930-00-840-1986

Rotary Switch - Page 2 of 2



Sty	عا	D	26	ia	n	a	ŧ٥	r	
JLY	ı	יש	ငၥ	щ		а	ιv	ш	

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A052b0