

View Online at <https://aerobasegroup.com/nsn/5930-00-840-3636>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Fungus proof and vibration resistant and moisture resistant and weatherproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.188 inches

**Body Length:**

0.500 inches

**Body Width:**

0.200 inches

**Body Height:**

0.350 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

0.062 inches

**Actuator Height:**

0.078 inches

**Actuator Free Position Height:**

0.047 inches

**Maximum Voltage Rating In Volts:**

90.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Pile-up Contact Form Arrangement:**

Z2a2c single position

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 16.000 milliamperes resistive ac

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0