

View Online at <https://aerobasegroup.com/nsn/5930-00-840-3636>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Fungus proof and vibration resistant and moisture resistant and weatherproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

0.500 inches

Body Width:

0.200 inches

Body Height:

0.350 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.062 inches

Actuator Height:

0.078 inches

Actuator Free Position Height:

0.047 inches

Maximum Voltage Rating In Volts:

90.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Pile-up Contact Form Arrangement:

Z2a2c single position

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 16.000 milliamperes resistive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0