NSN 5930-00-840-3664

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-840-3664 **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Corrosion resistant **Overall Length:** 2.190 inches **Overall Height:** 0.937 inches **Overall Width:** 0.937 inches **Body Diameter:** 0.937 inches **Bushing Length:** 0.437 inches **Actuator Diameter:** 0.375 inches **Actuator Height:** 0.390 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, both positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 3.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac **Thread Series Designator:** Unef **Terminal Type And Quantity:** 8 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5930-00-840-3664

Push Switch - Page 2 of 2



Fiig:

A053a0