NSN 5930-00-840-5040

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Between 0.998 inches and 1.002 inches

Body Style:Hole mounted

Dustproof

Overall Length: 1.938 inches



View Online at https://aerobasegroup.com/nsn/5930-00-840-5040

Center To Center Distance Between Mounting Facilities Parallel To Length:

Overall Height:
1.271 inches
Overall Width:
0.688 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
1.234 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Free Position Height:
0.615 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
6.0 ounces
Switch Actuating Force:
13.0 ounces
Actuator Movement:
Between 0.218 pretravel inches and 0.531 overtravel inches and 0.025 differential inches

NSN 5930-00-840-5040

Sensitive Switch - Page 2 of 2



Contact Loa	d Current	Rating	At Maximum	Rated	Voltage:
JUIILAUL EUG	u cuiteiii	. ivatiliy	AL WIGAIIIIUIII	Nateu	Voltage.

750.000 milliamperes resistive dc and 25.000 amperes resistive ac

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0