NSN 5930-00-840-5040

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-840-5040

ł	Hole mounted
ł	Hazardous Locations/environmental Protection:
[Dustproof
(Overall Length:
	1.938 inches
(Center To Center Distance Between Mounting Facilities Parallel To Length
E	Between 0.998 inches and 1.002 inches
(Overall Height:
	1.271 inches
(Overall Width:
(0.688 inches
E	Body Length:
	1.938 inches
ł	Body Width:
(0.688 inches
ł	Body Height:
	1.234 inches
(Case Material:
F	Plastic
l	Unthreaded Mounting Hole Diameter:
(0.140 inches
1	Actuator Style:
F	Round
,	Actuator Diameter:
(0.094 inches
,	Actuator Free Position Height:
(0.615 inches
I	Maximum Voltage Rating In Volts:
4	460.0 ac and 250.0 dc
I	nclosure Type:
F	Fully enclosed
ľ	Mounting Method:
ι	Jnthreaded hole
ľ	Nonpile-up Contact Arrangement:
2	2 pole, double throw, one position momentary single switch unit
Ş	Switch Release Force:
6	6.0 ounces
Ş	Switch Actuating Force:
	13.0 ounces
	Actuator Movement:

Between 0.218 pretravel inches and 0.531 overtravel inches and 0.025 differential inches

NSN 5930-00-840-5040

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

750.000 milliamperes resistive dc and 25.000 amperes resistive ac

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0