

View Online at <https://aerobasegroup.com/nsn/5930-00-841-3398>

Thread Class:

3a single pressure connection

Overall Length:

3.410 inches

Outside Diameter:

0.438 inches single connection

Body Length:

1.890 inches

Overall Diameter:

1.820 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Inlet connection

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

200.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

4.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+25.00/+40.00 actuation point pounds per square inch and +25.00/+40.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

32.00 actuation point pounds per square inch gage and 28.00 deactuation point pounds per square inch gage and 4.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Inverted flare, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0