

View Online at <https://aerobasegroup.com/nsn/5930-00-841-6291>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.310 inches

Overall Height:

2.212 inches

Overall Width:

0.750 inches

Bushing Length:

0.442 inches

Body Length:

1.310 inches

Body Width:

0.750 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.620 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Mounting Surface To Terminal End Distance:

1.062 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 9.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0