

View Online at <https://aerobasegroup.com/nsn/5930-00-842-2719>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

7.500 inches

Overall Height:

3.500 inches

Overall Width:

5.500 inches

Body Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

2.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

50.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Calibrated scale

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

6000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

10.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+325.00/+3000.00 actuation point pounds per square inch and +250.00/+2750.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

460.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0