

View Online at <https://aerobasegroup.com/nsn/5930-00-842-7251>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

0.876 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.695 inches

Overall Width:

0.346 inches

Body Length:

0.876 inches

Body Width:

0.346 inches

Body Height:

0.600 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.078 inches

Actuator Height:

0.050 inches

Actuator Free Position Height:

0.425 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Strategic weapon systems (poseidon & trident)

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

17.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Six foot wire leads

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0