# NSN 5930-00-842-9200

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-842-9200

# Body Style:

Hole mount

# **Overall Length:**

1.460 inches

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.720 inches

# **Overall Height:**

1.469 inches

#### **Overall Width:**

1.375 inches

#### **Bushing Length:**

0.375 inches

#### Body Length:

0.703 inches

#### **Body Width:**

1.375 inches

# Body Height:

1.422 inches

#### 1.422 1101103

Case Material:

# Metal

# Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches

# Actuator Style:

Round

# Actuator Diameter:

Between 0.281 inches and 0.343 inches

# **Actuator Height:**

Between 0.532 inches and 0.594 inches

# Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Threaded hole

# Thready Qty Per Inch (tpi):

40

# Thread Size:

0.112 inches

# Nonpile-up Contact Arrangement:

5 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

# NSN 5930-00-842-9200

Push Switch - Page 2 of 2

**Thread Series Designator:** 

Unc

# Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A053a0

