NSN 5930-00-843-6030

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-843-6030

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
1.370 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Overall Height:
1.165 inches
Overall Width:
0.406 inches
Body Length:
1.370 inches
Body Width:
0.406 inches
Body Height:
0.905 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.123 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Style:
Leaf
Actuator Free Position Height:
0.615 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
3.0 ounces
Switch Actuating Force:
32.0 ounces

Actuator Movement:

0.035 pretravel inches and 0.015 overtravel inches and 0.024 differential inches

NSN 5930-00-843-6030

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A053a0

Demilitarization: