

View Online at <https://aerobasegroup.com/nsn/5930-00-843-8990>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Vaportight

Bushing Length:

Between 0.450 inches and 0.490 inches

Body Length:

1.270 inches

Body Width:

0.635 inches

Body Height:

0.910 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.400 inches and 0.440 inches

Actuator Height:

Between 1.030 inches and 1.070 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Center position locked out

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Mrap - common nsn - used on rg33 cat i and 59 other weapon systems

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0