

View Online at <https://aerobasegroup.com/nsn/5930-00-844-4920>

Body Style:

Bushing/hole mounted

Overall Length:

Between 0.845 inches and 0.905 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.365 inches and 0.385 inches

Overall Height:

2.467 inches

Overall Width:

Between 0.657 inches and 0.719 inches

Bushing Length:

0.859 inches

Body Length:

Between 0.845 inches and 0.905 inches

Body Height:

1.062 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.198 inches and 0.200 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

Between 1.345 inches and 1.405 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

Between 0.970 inches and 1.030 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

23.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.250 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0