

View Online at <https://aerobasegroup.com/nsn/5930-00-844-6514>

**Body Style:**

Bushing mount

**Overall Length:**

0.840 inches

**Overall Height:**

2.157 inches

**Overall Width:**

0.719 inches

**Bushing Length:**

0.470 inches

**Body Length:**

0.840 inches

**Body Width:**

0.719 inches

**Body Height:**

Between 0.997 inches and 1.097 inches

**Actuator Style:**

Round

**Actuator Height:**

0.640 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and down position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position no locking action and center position locked in

**Maximum Voltage Rating In Volts:**

240.0 ac and 30.0 dc

**End Application:**

Qatarawa class lha, forrestal class cv, spruance class d (963), nimitz class cvn, wasp class lhd, virginia class cgn (41), kidd class ddg; fire control system, missile mk 74 (fcs); radar set, lightweight 3d (an/tps-59)

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0