

View Online at <https://aerobasegroup.com/nsn/5930-00-844-6514>

Body Style:

Bushing mount

Overall Length:

0.840 inches

Overall Height:

2.157 inches

Overall Width:

0.719 inches

Bushing Length:

0.470 inches

Body Length:

0.840 inches

Body Width:

0.719 inches

Body Height:

Between 0.997 inches and 1.097 inches

Actuator Style:

Round

Actuator Height:

0.640 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and down position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

240.0 ac and 30.0 dc

End Application:

Qatarawa class lha, forrestal class cv, spruance class d (963), nimitz class cvn, wasp class lhd, virginia class cgn (41), kidd class ddg; fire control system, missile mk 74 (fcs); radar set, lightweight 3d (an/tps-59)

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0