

View Online at <https://aerobasegroup.com/nsn/5930-00-844-6986>

**Thread Class:**

3a single pressure connection

**Thread Length:**

0.642 inches single pressure connection and 0.672 inches single pressure connection

**Overall Length:**

2.500 inches

**Outside Diameter:**

0.750 inches single connection

**Body Length:**

1.156 inches

**Overall Diameter:**

1.125 inches

**Pressure Switch Type:**

Gage

**Width Across Flats:**

1.250 inches

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Mounting Method:**

Threaded bushing

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

200.00 pounds per square inch

**Thread Size:**

0.750 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Sensing Element Burst Pressure:**

350.00 pounds per square inch

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

4.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

10.50 actuation point pounds per square inch and 7.50 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0