## NSN 5930-00-845-4587

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-845-4587

| Inside Diameter:   |
|--|
| 0.250 inches single connection   |
| Overall Length:  |
| 4.500 inches   |
| Overall Height:  |
| 4.844 inches   |
| Overall Width:   |
| 2.750 inches   |
| Body Height:   |
| 3.875 inches   |
| Distance Between Mounting Facility Centers:  |
| 1.938 inches   |
| Pressure Switch Type:  |
| Gage   |
| Operating Tempurature Rating:  |
| Between -20.0 degrees fahrenheit and 150.0 degrees fahrenheit  |
| Mounting Method:   |
| Inlet connection and unthreaded hole   |
| Features Provided:   |
| Calibrated scale   |
| Thready Qty Per Inch (tpi):  |
| 18 single pressure connection  |
| Contact Action Stimulus:   |
| Increase   |
| Proof Pressure:  |
| 25.00 pounds per square inch   |
| Thread Size:   |
| 0.250 inches single pressure connection  |
| Mounting Facility Pattern:   |
| Two position in-line   |
| Nonpile-up Contact Arrangement:  |
| 2 pole, single throw, normally open, momentary action  |
| Terminal Type:   |
| Screw  |
| Contact Load Current Rating:   |
| 5.0 amperes resistive load first voltage   |
| Contact Adjustability:   |
| Deactuation point adjustable and actuation point adjustable  |
| Contact Adjustment Range:  |
| +2.00/+15.00 actuation point pounds per square inch and +1.00/+6.00 deactuation point pounds per square inch |

## **Contact Adjustment Type:**

External actuation point screw and external deactuation point pointer with scale

## NSN 5930-00-845-4587

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator: Rectangular Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: ---

**Demilitarization:** 

No Fiig: A048b0