NSN 5930-00-845-7309

Sensitive Switch - Page 1 of 2



Constitute Owner Trage Total
View Online at https://aerobasegroup.com/nsn/5930-00-845-7309
Body Style:
Hole mounted
Overall Length:
1.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.497 inches and 0.503 inches
Overall Height:
0.940 inches
Overall Width:
0.690 inches
Body Length:
Between 1.235 inches and 1.265 inches
Body Width:
Between 0.510 inches and 0.540 inches
Body Height:
Between 0.860 inches and 0.890 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.100 inches and 0.103 inches
Actuator Length:
Between 0.365 inches and 0.395 inches
Actuator Style:
Rectangular
Actuator Height:
0.065 inches
Actuator Width:
Between 0.195 inches and 0.225 inches
Actuator Free Position Height:
Between 0.170 inches and 0.200 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

36.0 ounces

NSN 5930-00-845-7309

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage	Contact Load	Current Rating	At Maximum	Rated	Voltage
--	--------------	-----------------------	------------	-------	---------

10.000 amperes resistive ac

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0