NSN 5930-00-845-7309

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-845-7309

Body Style:

Hole mounted

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.497 inches and 0.503 inches

Overall Height:

0.940 inches

Overall Width:

0.690 inches

Body Length:

Between 1.235 inches and 1.265 inches

Body Width:

Between 0.510 inches and 0.540 inches

Body Height:

Between 0.860 inches and 0.890 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.103 inches

Actuator Length:

Between 0.365 inches and 0.395 inches

Actuator Style:

Rectangular

Actuator Height:

0.065 inches

Actuator Width:

Between 0.195 inches and 0.225 inches

Actuator Free Position Height:

Between 0.170 inches and 0.200 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

36.0 ounces

NSN 5930-00-845-7309

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0