NSN 5930-00-847-8631

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-847-8631

External deactuation point screw and external actuation point screw

Overall Length:
5.000 inches
Overall Height:
5.813 inches
Overall Width:
2.688 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.812 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+5.00/+75.00 actuation point pounds per square inch and +5.00/+75.00 deactuation point pounds per square inch
Contact Adjustment Type:

NSN 5930-00-847-8631

Pressure Switch - Page 2 of 2

No Fiig: A048b0



Contact Voltage Rating In Volts: 550.0 dc at sea level third voltage Pressure Connector Type: Swivel nut, gasket seal, threaded internal single connection Media For Which Designed: Liquid Style Designator: Rectangular Thread Series Designator: Unf single pressure connection Shelf Life: N/a Unit Of Measure: - Demilitarization: