

View Online at <https://aerobasegroup.com/nsn/5930-00-848-7475>

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

5.250 inches

**Overall Height:**

6.000 inches

**Overall Width:**

3.500 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.562 inches

**Longest Vertical Distance Between Mounting Centers:**

3.500 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Flush and threaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

20 all threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

10.0 amperes resistive load second voltage and 10.0 amperes inductive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+300.00/+3000.00 actuation point pounds per square inch and +200.00/+2700.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Voltage Rating In Volts:**

450.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A048b0